

Specter Gen II Wireless LED Light Single Light 5000 Lumens

The United Shield Gen II Wireless LED is the next generation in wireless LED shield lights introduced into the market. This next gen light is fully removable from the shield, 1/3 of the size and offers a 62.5% weight reduction from the first generation. With the use of low transmitting wireless signal, wires are no longer needed to penetrate or go around a shield. The light has one built in rechargeable lithium ion battery. The light features a single, 5000 Lumen LED light with 3 functional modes (Constant on, Constant turbo-strobe and Green lowlight navigation). With the use of an integrated battery, there is no longer a need for a rear battery pack. The light comes standard with a pressure pad and a remote controller. The pressure pad that can be placed on the handle to assist in ease of turning the light on and off.

Lights are able to be factory integrated or retro-fit to existing United Shield International shields.



United Shield Wireless LED light with 3 functions; Constant on, Constant turbo Strobe and low light green navigation

- -Waterproof
- -Runtime of 3 hours at steady burn- 100% output, then reduction to 50% output for an additional 2.5 hours
- -Battery operated with rechargeable Lithium battery
- -Total Weight of system 1.46 lbs (battery included)
- Reduced Size 1/3 of size of gen I
- Max Beam Distance 303 ft
- Wireless Range 100 ft
- Fully Removeable
- Upgraded pressure pad with field serviceable battery access (Cr123)
- Magnetic charging

5000 Lumen System 212 White LED Light heads 165° spread

The second of th





Light Overview Video QR code below

Warranty and Quality Assurance

United Shield offers a two year warranty on manufacturer defects. United Shield manufactures in accordance with ISO9001 & ISO14001 quality standard







North America
United Shield International LLC
891 Hughes Dr. Traverse City
MI 49696,USA
Phone: +1 231 933 1179, Fax: +1 231 933 5368
Email: bbanducci@unitedshield.com
www.us.unitedshield.com

